

MODEL **TR 12.8-110 Li-ion**  
 VOLTAGE **12.8V**  
 NOMINAL CAPACITY **110Ah (1,400 Wh)**  
 CASE **PC/PBT Resin Blend, IP67 Enclosure, UL94 V-0**  
 BATTERY **Deep-Cycle Lithium Iron Phosphate**  
 COLOR **Maroon**  
 CYCLE LIFE **>5,000 Cycles @ 80% DOD\***  
 INTELLIGENCE **Integrated Microprocessor, State of Charge Gauge,  
 Integrated Contactor, Current Sensor, Fuse**



## 12.8 VOLT

### PHYSICAL SPECIFICATIONS

BCI	Model	Terminal Type	Dimensions Inches (mm)			Weight Lbs. <sup>A</sup> (kg)	Handles	Installation Orientation
			Length	Width	Height			
Group 27	TR 12.8 - 110	5/16" - 18 Stud and 1/4" - 20 Threaded Hole	12.1 (307)	6.6 (168)	8.7 (221)	30 (13.6)	Molded	Horizontal and Vertical

### ELECTRICAL SPECIFICATIONS

Voltage	Capacity Amp-Hours (Ah)			Energy (kWh)	Short Circuit Current (A)
	5-Hr (22A)	10-Hr (11A)	20-Hr (5.5A)		
12.8V	110	110	111	20-Hr 1.4	Fused at 500 Amps

### OPERATIONAL DATA

Operating Temperature Range	Storage Temperature Range
-4°F to 140°F (-20°C to 60°C) At Temperatures Below 32°F (0°C) Charging Current Reduced	-40°F to 140°F (-40°C to 60°C)

### CHARGING INSTRUCTIONS

Charger Settings	
Recommended Charging Voltage	14.4 - 14.8 V
Recommended Float Voltage	13.8 V
Maximum Charging Current @ Temperature	
> 32° F (0°C)	110 A
14° to 32° F (-10° to 0°C)	15 A
-4° to 14°F (-20° to -10°C)	6 A

### OTHER SPECIFICATIONS

Electrical Features	
Continuous Discharge Current	300 Amps
Pulse Discharge Current @ 77°F (25°C)	400 Amps for 30 Seconds
Communication	N/A
Reserve Capacity @ 25 Amps	265 Min
BMS Protections	Cell-Level Voltage, Temperature, Over Voltage, Under Voltage, Over-current
BMS Functions	Cell Balancing, State of Charge
Safety Systems	Contactor, Fuse, BMS
Series Connections	Up to 4S (51.2V)
Parallel Connections	Up to 20P
Discharge Voltage Cutoff	9.5V ± 5%
Charge Voltage Cutoff	15.2V ± 5% for 5 Seconds
Data Logging	Total Lifetime Amp Hours, Recent Faults
Other Features	
Environmental Protection	IP67
Shipping Classification	UN3480, Class 9, UN38.3 Certified
Case Flame Rating	Non-Flammable UL94 V-0

### RECYCLE RESPONSIBLY




**Do not mix with Lead Acid Batteries when Recycling.**


\*To 70% of Initial Capacity.

**NOTE:** See Trillium User's Guide for Proper Operation.


## CYCLE LIFE




## AVAILABLE CAPACITY



## CYCLE LIFE VS. TEMPERATURE




## G27 DISCHARGE CAPACITY



## BATTERY DIMENSIONS

Dimensions Inches (mm) - shown with M8 and Stud



## TERMINAL CONFIGURATIONS<sup>B</sup>

### Stud



Bolt:  
1/4 - 20 x 0.23" Threaded Hole &  
5/16 - 18 x 0.625" Threaded Stud

## SAFETY/AGENCY INFORMATION

### Certified to the Following

UN/DoT 38.3	IEC62133
ROHS Compliant	UL2271 (Q1 2019)*
TUV*	UL1642 (Cells)

\*Pending

UN38.3 PASSED  
TRANSPORTATION  
SAFETY  
CERTIFIED



TROJAN BATTERY  
COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV  
= ISO 9001:2015 =

A. Weight may vary.  
B. Terminal images are representative only.

## STATE OF CHARGE INDICATOR (GAUGE)

Trillium Group 24 and Group 27's built-in smart battery features include a battery status push button and indicator light on the top of the case. After the button is pressed, the indicator light will show one of the following color patterns for five seconds:

Light Color Pattern	Battery Condition	Gauge
Solid Green	90% - 100% Capacity Remaining	
Blinking Green	50% - 90% Capacity Remaining	
Solid Yellow	35% - 50% Capacity Remaining	
Blinking Yellow	20% - 35% Capacity Remaining	
Solid Red	10% - 20% Capacity Remaining	
Blinking Red	0% - 10% Capacity Remaining	
Blinking Green and Red	Battery is shut off	

**NOTE:** Consult Trillium User's Guide for more information at [trojanbattery.com](http://trojanbattery.com).