

MODEL **TR 12.8-92 Li-ion**
 VOLTAGE **12.8V**
 NOMINAL CAPACITY **92Ah (1,180 Wh)**
 CASE **PC/PBT Resin Blend, IP67 Enclosure, UL94 V-0**
 BATTERY **Deep-Cycle Lithium Iron Phosphate**
 COLOR **Maroon**
 CYCLE LIFE **>5,000 Cycles @ 80% DOD***
 INTELLIGENCE **Integrated Microprocessor, State of Charge Gauge, Integrated Contactor, Current Sensor, Fuse**



12.8 VOLT

PHYSICAL SPECIFICATIONS

BCI	Model	Terminal Type	Dimensions Inches (mm)			Weight Lbs. ^A (kg)	Handles	Installation Orientation
			Length	Width	Height			
Group 24	TR 12.8 - 92	M8 - 1.25 Threaded Hole	10.2 (259)	6.6 (168)	8.5 (216)	27 (12.3)	Molded	Horizontal and Vertical

ELECTRICAL SPECIFICATIONS

Voltage	Capacity Amp-Hours (Ah)			Energy (kWh)	Short Circuit Current (A)
	5-Hr (18A)	10-Hr (9A)	20-Hr (4.6A)	20-Hr	
12.8V	92	92	92.5	1.18	Fused at 400 Amps

OPERATIONAL DATA

Operating Temperature Range	Storage Temperature Range
-4°F to 140°F (-20°C to 60°C) At Temperatures Below 32°F (0°C) Charging Current Reduced	-40°F to 140°F (-40°C to 60°C)

CHARGING INSTRUCTIONS

Charger Settings	
Recommended Charging Voltage	14.4 - 14.8 V
Recommended Float Voltage	13.8 V
Maximum Charging Current @ Temperature	
> 32° F (0°C)	92 A
14° to 32° F (-10° to 0°C)	12.5 A
-4° to 14°F (-20° to -10°C)	5 A

OTHER SPECIFICATIONS

Electrical Features	
Continuous Discharge Current	250 Amps
Pulse Discharge Current @ 77°F (25°C)	350 Amps for 30 Seconds
Communication	CAN-Open
Reserve Capacity @ 25 Amps	220 Min
BMS Protections	Cell-Level Voltage, Temperature, Over Voltage, Under Voltage, Over-current
BMS Functions	Cell Balancing, State of Charge
Safety Systems	Contactor, Fuse, BMS
Series Connections	Up to 4S (51.2V)
Parallel Connections	Up to 20P
Discharge Voltage Cutoff	9.5V ± 5%
Charge Voltage Cutoff	15.2V ± 5% for 5 Seconds
Data Logging	Total Lifetime Amp Hours, Recent Faults
Other Features	
Environmental Protection	IP67
Shipping Classification	UN3480, Class 9, UN38.3 Certified
Case Flame Rating	Non-Flammable UL94 V-0

RECYCLE RESPONSIBLY




Do not mix with Lead Acid Batteries when Recycling.


*To 70% of Initial Capacity.

NOTE: See Trillium User's Guide for Proper Operation.


CYCLE LIFE




AVAILABLE CAPACITY



CYCLE LIFE VS. TEMPERATURE





G24 DISCHARGE CAPACITY



BATTERY DIMENSIONS

Dimensions Inches (mm) - shown with M8



Ask your Trojan Representative for an accessory to match the height of the Trojan T-105 Battery. Note: Available in 2019

TERMINAL CONFIGURATIONS^B

M8



M8 - 1.25 x 9 mm Threaded Hole

SAFETY/AGENCY INFORMATION

Certified to the Following

UN/DoT 38.3	IEC62133
ROHS Compliant	UL2271 (Q1 2019)*
TUV*	UL1642 (Cells)

*Pending

UN38.3 PASSED
TRANSPORTATION
SAFETY
CERTIFIED



TROJAN BATTERY
COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001:2015 =

A. Weight may vary.
B. Terminal images are representative only.

STATE OF CHARGE INDICATOR (GAUGE)

Trillium Group 24 and Group 27's built-in smart battery features include a battery status push button and indicator light on the top of the case. After the button is pressed, the indicator light will show one of the following color patterns for five seconds:

Light Color Pattern	Battery Condition	Gauge
Solid Green	90% - 100% Capacity Remaining	
Blinking Green	50% - 90% Capacity Remaining	
Solid Yellow	35% - 50% Capacity Remaining	
Blinking Yellow	20% - 35% Capacity Remaining	
Solid Red	10% - 20% Capacity Remaining	
Blinking Red	0% - 10% Capacity Remaining	
Blinking Green and Red	Battery is shut off	

NOTE: Consult Trillium User's Guide for more information at trojanbattery.com.

COMMUNICATIONS CONNECTOR

Battery Side	User Side
Deutsch DTM04-3P	Deutsch DTM06-3S
Pin 1: GND/B-	Pin 1: GND/B-
Pin 2: CAN H	Pin 2: CAN H
Pin 3: CAN L	Pin 3: CAN L



800.423.6569 / +1.562.236.3000 / trojanbattery.com

TRJN_24_Lithium_12.8-92_102618_A4

© 2018 Trojan Battery Company, LLC. All rights reserved. Trojan Battery Company is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Trojan Battery Company reserves the right to make adjustments to this publication at any time, without notice or obligation.