




Specifications

Rated Voltage		12V
Nominal Capacity	5.4Ah	(C ₂₀ ,1.75V/cell)
Dimension	Length Width Container Height Total Height	90±1mm (3.54 inches) 70±1mm (2.76 inches) 101±2mm (3.98 inches) 107±2mm (4.21 inches)
Approx Weight		1.80 Kg (3.96 lbs)
Terminal		T1/T2
Container Material		ABS
Rated Capacity (25°C)	5.40 Ah 5.11 Ah 4.65 Ah 4.14 Ah 3.68 Ah	(20hr,0.270A,1.80V/cell) (10hr,0.511A,1.80V/cell) (5hr,0.929A,1.75V/cell) (3hr,1.38A,1.75V/cell) (1hr,3.68A,1.60V/cell)
Max. Discharge Current		81A (5s)
Internal Resistance (25°C)		Approx 25mΩ
Operating Temp.Range	Discharge Charge Storage	-15 ~ 50°C (5 ~ 122°F) 0 ~ 40°C (32 ~ 104°F) -15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range		25±3°C (77±5°F)
Cycle Use	Initial Charging Current less that 14.4V~15.0V at 25°C(77°F)Tem	
Standby Use	Initial Charging Current less that 13.5V~13.8V at 25°C(77°F)Tem	· ·
Effect of temp. to Capacity	40°C (104°F) 25°C (77°F) 0°C (32°F)	103% 100% 86%
Self Discharge	LP series batteries may be stored at 25°C(77°F) and then a freshen For higher temperatures the time	ing charge is required.



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)																
F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	17.9	12.7	9.79	7.96	5.76	4.14	3.33	2.40	1.85	1.33	1.06	0.905	0.775	0.610	0.499	0.264
1.80V/cell	19.2	13.4	10.3	8.28	5.94	4.25	3.41	2.45	1.88	1.36	1.08	0.918	0.787	0.619	0.506	0.267
1.75V/cell	20.3	14.0	10.6	8.51	6.09	4.34	3.48	2.49	1.92	1.38	1.09	0.929	0.796	0.626	0.511	0.270
1.70V/cell	21.2	14.5	11.0	8.76	6.25	4.44	3.55	2.53	1.95	1.40	1.11	0.942	0.805	0.632	0.516	0.272
1.67V/cell	22.0	15.0	11.2	8.94	6.36	4.51	3.60	2.57	1.97	1.41	1.12	0.950	0.812	0.637	0.520	0.274
1 60\//ooll	22.2	15.6	11.6	0.20	6.53	4.62	2.69	2.62	2.01	1 11	1 1/	0.066	0.834	0.646	0.526	0.277

Constant Power Discharge (Watts/cell) at 25 °C (77°F)																
F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	33.8	24.1	18.7	15.3	11.1	8.03	6.48	4.68	3.62	2.62	2.09	1.79	1.53	1.21	0.992	0.528
1.80V/cell	36.0	25.4	19.5	15.9	11.4	8.22	6.62	4.76	3.68	2.66	2.12	1.81	1.55	1.23	1.00	0.534
1.75V/cell	37.5	26.2	20.1	16.2	11.7	8.36	6.72	4.83	3.73	2.70	2.15	1.83	1.57	1.24	1.01	0.540
1.70V/cell	38.9	27.1	20.6	16.6	11.9	8.52	6.83	4.91	3.78	2.73	2.17	1.85	1.59	1.25	1.02	0.544
1.67V/cell	40.0	27.7	21.1	16.9	12.1	8.63	6.92	4.96	3.81	2.75	2.19	1.87	1.60	1.26	1.03	0.549
1.60V/cell	41.6	28.5	21.6	17.3	12.4	8.79	7.04	5.04	3.88	2.80	2.22	1.89	1.62	1.28	1.04	0.555

LP Series-General Purpose LP12-5.4(12V5.4Ah)



Applications

- All purpose
- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- · Alarm and security system
- Communication power supply
- DC power supply
- · Auto control system


General Features

- 5 years design life(25°C)
- Special exhaust structure and sealing technology, safe and reliable, flexible installation, convenient maintenance
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- High quality AGM separator: extend cycle life and prevent micro short circuit
- High purity raw material: ensure low self discharge rate


Standards

- Compliance with IEC 60896 standards, EU Battery Directive
- UL, CE Certified
- Manufactured in Leoch®IATF16949, ISO45001,ISO 9001 and ISO 14001 certified production facilities


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Canacity



Float Service Life



Sales Offices Worldwide

China Sales Office

5th Floor, Xinbaohui Bldg., Nanhai Blvd., Nanshan, Shenzhen, China. 518052 Tel: +86-755-86036060 (100 lines) Fax: +86-755-26067269 E-mail:export@leoch.com

North America Sales Office

19751 Descartes Foothill Ranch, CA 92610, USA Tel: 949-588-5853 Fax: 949-588-5966 E-mail: sales@leoch.us Http://www.leoch.us

HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road Tsuen Wan, New Territories, Hong Kong Tel: +852 35786666 Fax: +44 1452 690125 E-mail: sales.hk@leoch.com

UK Sales Office

9B Wheatstone Court. Waterwells, Business Park, Gloucester, GL2-2AQ, UK United Kingdom Tel: +44(0) 1452 729428 / 1452 729696 Fax:+44 1452 690125 E-mail: Sales.Europe@leoch.com Http://www.leoch.eu

Singapore Sales Office

No. 1 Tech Park Crescent, Singapore 638131 Tel: +65 68636078 Fax: +65 6863 6079 Email: sales.sg@Leoch.com

EMEA Sales Office

1 Deligiorgi St., 121 31 Athens, Greece Tel: +30 210 5760318 (2 lines) E-mail: support_EMEA@leoch.com Http://www.leoch.eu

Australia Sales Office

2 /29 Tarlington Place, Smithfield. NSW 2164 Australia Tel: 02 9756 0950 E-mail: sales.au@leoch.com

India Sales Office

Shed no.A-53(b), 2nd Stage of Peenya Industrial Area, Bangalore North Taluk, Bangalore-560058, India Tel: +91-80-23440018/23440019 Fax: +91-80-23440017 E-mail: indiasales@leoch.com

