

		AJ 275-12-S	AJ 350-24-S	AJ 400-48-S	AJ 500-12-S	AJ 600-24-S	AJ 700-48-S	AJ 1000-12-S	AJ 1300-24-S	AJ 2100-12-S	AJ 2400-24-S
Options											
Solar regulator	Voltage max.	25 Vdc	45 Vdc	90 Vdc	25 Vdc	45 Vdc	90 Vdc	25 Vdc	45 Vdc	25 Vdc	45 Vdc
	Current max.	10 Adc			15 Adc			25 Adc		30 Adc	
	Principle	Floating 3 stages (I/U/UO)									
	Absorption voltage	14.4 Vdc	28.8 Vdc	57.6 Vdc	14.4 Vdc	28.8 Vdc	57.6 Vdc	14.4 Vdc	28.8 Vdc	14.4 Vdc	28.8 Vdc
	Floating voltage	13.6 Vdc	27.2 Vdc	54.4 Vdc	13.6 Vdc	27.2 Vdc	54.4 Vdc	13.6 Vdc	27.2 Vdc	13.6 Vdc	27.2 Vdc
Plug for remote control (RCM)		•	•	•	•	•	•	•	•	•	•
Accessories											
JT8 Remote control											•

* 120Vac/60Hz on request

** Standby with solar option -S

Data may change without any notice